



# KUGA 2 GUNS DC EV CHARGING ADVERTISING STATION

60kW / 90kW / 120kW



# KUGA 2 GUNS DC CHARGING ADVERTISING STATION

60kW / 90kW / 120kW

## PRODUCT OVERVIEW

Remarkable 43-inch Advertising screen for effortless control. It comes with a range of certifications including CE, CB, UKCA, TUV, and RoHS, and offers robust full protection features. With convenient app control and Ethernet/4G connectivity, you can charge your EV with confidence and efficiency.



## PRODUCT ADVANTAGES



IP55 Rating



Ethernet/4G



Full Protection



OCPP 1.6J



RFID



App Control



Cable Management



43-inch advertising screen

# KUGA 2 GUNS DC EV CHARGING ADVERTISING STATION

60kW / 90kW / 120kW



Charger Station Units

BGDC60-D

BGDC90-D

BGDC120-D

## Structure Description

Shell Material	Sheet Metal		
Charger Unit Dimensions	700 x 520 x 1800 (LxWxT)		
Charger Unit Weight	≤500kG		
Installation Method	Floor-stand Type		
Cable Routing	Bottom Inlet Wiring, Outlet Wiring		
Cable Length	5 M		
Charging Outlets	Double(CCS1+CCS1) Double(CCS1+CHADEMO) Double(CCS2+GBT) Double(CHADEMO+CHADEMO)	Double(CCS2+CCS2) Double(CCS2+CHADEMO) Double(CHADEMO+GBT)	Double(CCS1+CCS2) Double(CCS1+GBT) Double(GBT+GBT)
Connectivity Authorization	RFID, App		
Screen	43-Inch Advertising Screen/LED Light		

## Electrical Specification

AC Input Voltage	AC380V±15%, 3P+N+PEAC		
Input Frequency	50Hz/60Hz		
Consumption	≤40W		
Rated Power	60KW	90KW	120KW
Output Voltage Range	CCS1/CCS2/GBT: 150 Vdc - 1000 Vdc; CHADEMO: 150Vdc-500Vdc		
Output Current	CCS1/CCS2/GBT:0-250A;CHADEMO:0-125A		
Efficiency	≥95%		
Power Factor	≥0.99 (load:100%)		





## Functionate Design

User Interface	Emergency Stop Button, LED Indicator, Card Swiping, Touch Screen
Charging Stands	IEC 61851-21-2:2021; IEC 61000-6-2019; EN61000-6-4:2019; IEC 61851-1:2019; EN 61851-23:2014; EN 61851-24:2014

## Communication

OCPP	OCPP 1.6J
Network Interface	Ethernet/4G

## Environment Condition

Application Place	Indoor/Outdoor
Working Latitude	<2000m
Working Temperature	-30°C - +50°C
Working Humidity	5% - 95%
Protection Level	IP55
Natural Cooling	Forced-air Cooling
Security Design	Over/Under Voltage Protection, Overload Protection, Current Leakage Protection, Grounding Protection, Over Temp Protection, Lightening Surge Protection